

**SUNELL 2MP/5MP DVR list**

ارديبهشت ماه ۱۴۰۲

Model	SN-ADR3304E1	SN-ADR3808E1	SN-ADR3316E1	SN-ADR3316E2	SN-ADR3816E2
	DVR4H	DVR8HG	DVR16H	DVR16HH	DVR16HF
picture					
Video and Audio					
Analog Camera Input	4ch BNC	8ch BNC	16ch BNC		
AHD/TVI/CVI Camera	5MP/4MP/3MP/1080P720P @25/30fps				
CVBS Camera	PAL/NTSC				
IP Camera Input	4ch, each channel up to 1080P	8ch, each channel up to 1080P	16ch, each channel up to 1080P		16ch each channel up to 5MP
Audio In/Out	1ch input, 1ch output, RCA			6ch input, 1ch output, RCA	
Two-way Talk	N/A				
Display					
Interface	1ch HD-OUT, 1ch VGA				
Resolution	HD-OUT: 3840x2160, 1920x1080, 1280x1024, 1440x900				
	VGA: 1920x1080, 1280x1024, 1440x900 & CVBS Output				
Multi-screen Display	1/4	1/4/9	1/4/9/16		
Recording					
Compression	H.265 / H.264				
Resolution	5MP-N, 4MP-N, 1080P, 720P, 960H, D1, CIF				
Record Rate	5MP-N@10fps, 4M@7fps, 1080P @15fps				4K-N@8fps, 5MP@7fps, 4MP@8fps, 1080P@15fps
Bit Rate	16Kbps~4096Kbps				
Record Mode	Manual, Event, Timer				
Record Interval	Post-record: 30 ~ 60 sec				
Video Detection and Alarm					
Trigger Events	Recording, Buzzer, Push message, Pop up message				
Video Detection	Motion Detection, Video Loss, Camera Tamper				
Alarm input	N/A			4/1	
Network					
Interface	1 RJ-45 port (10/100Mbps)				
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP				
Max. User Access	Access 4 users				
Smart Phone	iPhone, iPad, Android				
Interoperability	ONVIF, SDK, CGI				
Playback and Backup					
Playback	4,1	9,4,1	16,9,4,1		
Search Mode	Time /Date, Alarm, Picture grid, Event				
Playback Function	Play, Pause, Stop, Next Frame, Fast play, Slow Play, Layout, Shuffle, Backup Selection, Digital Zoom				
Storage					
Internal HDD	1 SATA Ports, up to 8TB for each HDD			2 SATA Ports, up to 8TB for each HDD	
eSATA	N/A				
Interface					
USB	2 ports (USB 2.0 x2)				
RS232	N/A				
RS485	N/A		1 Port, for PTZ Control		
General					
Power Supply	DC12V/2A			DC12V/4A	
Power Consumption	Max 10W (without HDD)	Max 15W (without HDD)	Max 10W (without HDD)		Max 15W (without HDD)
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)				
Dimensions (mm)	255(L) x 244(W) x 44(H)			350(L) x 305(W) x 49(H)	
Net Weight	900 g	1 Kg	1 Kg	1.8 Kg	