


Model	SN-NVR5004E1 (NVR4EC)	SN-NVR3804E1-P4-J (NVR4HPOE-AI) face, human, vehicle detection on AI cameras and capture
picture		
Video Input		
IP Camera Input	4 Channel	4 Channel with POE
Incoming Bandwidth		40 Mbps
Outgoing Bandwidth		40 Mbps
Video Output		
HDMI Output	1920 × 1080, 1280 × 1024, 1024 × 768	3840×2160,1920×1080, 1280×1024, 1024×768
VGA Output	1920×1080, 1280×1024, 1024×768	1920×1080, 1280×1024, 1024×768
Decoding Capacity	1ch 6MP, 4ch 1080P@30fps	1ch 8MP, 4ch 1080P@30fps
Dual Stream		Support
Multi-screen Display		1/4
Recoding		
Resolution	6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1
Recording Mode	Manual, Schedule (Regular, Continuous), Event	
Trigger Events	Motion Detection, Video Loss, Alarm in, IVS	
Playback and Backup		
Sync Playback	4/1	
Search Mode	Time /Date, Alarm, Picture grid, Event	
Backup Mode	USB Device, Network	
Alarm		
General Alarm	N/A	Motion Detection, Video Loss, Alarm in, Alarm out, IVS (by camera)
Abnormal Alarm	N/A	Disk Alarm, IP Address Conflict, Network Disconnect
Intelligent Analysis	N/A	Intrusion (support the accurate detection of vehicle and human)
Network		
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE	
Remote Users	8 users	
Storage		
HDD	1 sata Up to 10TB for each HDD	1 sata Up to 12TB for each HDD
Interface		
Network	1 × RJ-45, 10/100 Mbps self-adaptive Ethernet port	
PoE	N/A	4 Ports (IEEE 802.3af), 32W
HDMI	1	
VGA	1	
Audio I/O	N/A	1/1
Alarm I/O	N/A	4/1
USB	Rear panel: 2 × USB 2.0	3 ports (USB 2.0 × 3)
General		
Power Supply	DC12V/2A	DC48V/1.25A
Power Consumption	< 5 W (without HDD)	< 15 W (without HDD)
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)	
Storage Conditions	Less than 90% RH	
Dimensions	254.5 × 224.4 × 43.9 mm	255 × 237 × 47.5 mm
Net Weight	0.62 kg without HDD	0.9 kg (1.98 lb) without HDD