



32ch Hybrid DVR

اردیبهشت ماه ۱۴۰۲



System

Model	SN-ADR3332E4 (DVR32H5)
Picture	

Video and Audio

Analog Camera Input	32ch BNC
AHD Camera	5MP/4MP/3MP/1080P720P @25/30fps
TVI Camera	5MP/4MP/3MP/1080P720P @25/30fps
CVI Camera	5MP/4MP/3MP/1080P720P @25/30fps
CVBS Camera	PAL/NTSC
IP Camera Input	32ch, each channel up to 1080P
Audio In/Out	16ch input, 1ch output, RCA
Two-way Talk	N/A

Display

Interface	1 HD-OUT, 1 VGA
Resolution	HD-OUT: 3840x2160, 1920x1080, 1440x900, 1280x1024 VGA: 1920x1080, 1280x1024, 1280x720
Multi-screen Display	1/4/8/9/16/32/36

Recording

Compression	H.265 / H.264
Resolution	5MP, 4MP, 1080P, 720P, D1, CIF
Record Rate	5MP@6fps, 4MP@7fps, 1080P@15fps
Bit Rate	Main stream: 128Kbps~6144Kbps Sub stream: 16Kbps~1024Kbps
Record Mode	Manual, Event, Timer
Record Interval	Post-record: 30 ~ 60 sec

Video Detection and Alarm

Trigger Events	Recording, Buzzer, Push message, Pop up message
Video Detection	Motion Detection, Video Loss, Camera Tamper
Alarm in/out	16/4

Playback and Backup

Playback	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Playback Function	Play, Pause, Stop, Next Frame, Fast play, Slow Play, Layout, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB HDD

Network

Interface	1 RJ-45 port (10/100/1000Mbps)
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP
Max. User Access	Access 4 users

Storage

Internal HDD	4 SATA Ports, up to 8TB for each HDD
eSATA	N/A

Interface

USB	2 ports (USB 2.0 x2)
RS232	N/A
RS485	1 Port, for PTZ Control

General

Power Supply	DC12V/6A
Power Consumption	Max 10W (without HDD)
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Dimensions	440mm(L) x 400.5mm(W) x 60mm(H)
Net Weight	4kg