

**4K SUNELL DVR list**

تیرماه ۱۴۰۵



Model	SN-ADR3908E1 (DVR8K4)	SN-ADR3916E2 (DVR16K4)
picture		
Video and Audio		
Analog Camera Input	8ch BNC	16ch BNC
AHD/TVI/CVI Camera	4K/5MP/4MP/3MP/1080P/720P @25/30fps	
CVBS Camera	PAL/NTSC	
IP Camera Input	8ch each channel up to 5MP	16ch each channel up to 8MP
Audio In/Out	4ch input, 1ch output, RCA & Audio on Coaxial Support	
Display		
Interface	1ch HD-OUT, 1ch VGA, 1ch CVBS	
Resolution	HD-OUT: 3840×2160, 1920×1080, 1280×1024, 1440×900	
	VGA: 1920×1080, 1280×1024, 1440×900	
Multi-screen Display	1/4/8	1/4/9/16
Recording		
Compression	H.265 / H.264	
Resolution	4K, 5MP, 4MP, 1080P, 720P, 960H, D1, CIF	
Record Rate	4K@7fps, 5MP@12fps, 4MP@15fps, 1080P@30fps	4K@7fps, 5MP@12fps, 4MP@15fps, 1080P@30fps
Bit Rate	128Kbps~6144Kbps	
Record Mode	Manual, Event, Timer	
Record Interval	Post-record: 30 ~ 60 sec	
Video Detection and		
Trigger Events	Recording, Buzzer, Push message, Pop up message	
Video Detection	Motion Detection, Video Loss, Camera Tamper	
Alarm in/out	N/A	8/1
Network		
Interface	1 RJ-45 port (10/100Mbps)	
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP	
Max. User Access	Access 4 users	
Smart Phone	iPhone, iPad, Android	
Interoperability	ONVIF, SDK, CGI	
Playback and Backup		
Playback	8/4/1	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event	
Playback Function	Play, Pause, Stop, Next Frame, Fast play, Slow Play, Layout, Shuffle, Backup Selection, Digital Zoom	
Backup Mode	USB HDD	
Storage		
Internal HDD	1 SATA Ports up to 8TB for each HDD	2 SATA Ports up to 8TB for each HDD
eSATA	N/A	
Interface		
USB	2 ports (USB 2.0 x2)	
RS485	1 Port, for PTZ Control	
General		
Power Supply	DC12V/2A	DC12V/4A
Power Consumption	Max 10W (without HDD)	Max 15W (without HDD)
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)	
Storage Conditions	Less than 90% RH	
Dimensions(mm)	255(L) x 225(W) x 44(H)	350(L) x 305(W) x 49(H)
Net Weight	750g	1.8Kg